Miniature Color Camera With Integral LED Lighting

The NOVA is a miniature, color CCD video camera with an integral light ring. It is ideal for mounting on ROV manipulators, for down-hole video and for remote tooling applications where providing external lighting is difficult if not impossible.

It has a high resolution color CCD sensor providing outstanding picture quality and performance in a very compact housing. The integral light ring illuminates objects up to several feet away.

The camera has a fixed focus, wide angle lens and requires no external controls in normal operation. Optional control of the LED lighting can be provided. Ideal for applications where size is of critical importance, but high image quality is also a requirement.



Features

- ☐ High Resolution Color CCD Module
- Integral LED Light Ring
- ☐ Fixed Focus, Wide Angle Lens
- Extremely Compact Titanium Pressure Housing
- 4,000 Meter Depth Rating


Applications

- ROV Manipulator Arm
- ☐ Remote Tooling Systems
- Diver Use
- Inspection ROV
- Leisure Marine



Insite Pacific - NOVA

Specification



All measurements in inches (millimeters)

Electrical

Sensor 1/3 Inch EXview HAD CCD II
Resolution 700 Horizontal TV lines

Minimum Illumination 0.001 Lux (Faceplate) Iris CCD Iris, NTSC 1/60 to 1/100,000 Sec.

PAL 1/50 to 1/100,000 Sec.

Signal to Noise Ratio >50 dB (AGC off)
Total Pixels PAL (50Hz), 1020(H) x 596(V)

NTSC (60Hz), 1020(H) x 508(V)

Video Output Composite 1Vpp
Camera Power 15 to 30VDC at 175mA typical

12VDC Optional

Environmental

Depth 4000 meters (13,000ft)
Operating Temperature-10°C to 50°C (14°F to 122°F)

Storage Temperature -20°C to 60°C (-4°F to 140°F)

Mechanical

Pressure Housing 4000m Operating Depth

Titanium Pressure Housing

Size Refer to drawing for detailed dimensions Length 9.7cm (3.82 inches)

excluding underwater connector

Diameter 4.0cm (1.58 inches)

Optical

Lens 4.3mm Focus Range 178mm (7 inches) to infinity

Field of View 59° Diagonal

49° Horizontal 38° Vertical Weight in air 0.37kg (13oz)

Weight in water 0.26kg (9oz)
Housing Material 6AL / 4V Titanium
Pressure Window Optically Polished Sapphire

Connector Customer specified

All specifications are subject to change in line with Insite Pacific's policy of continual product development.

Insite Pacific Inc.

6837 Nancy Ridge Drive, Suite G, San Diego, California, 92121, USA Phone (858) 523-0642 Fax (858) 523-0643

Website: www.insitepacific.com Email: sales@insitepacific.com